



6" 26W – 42W Compact Fluorescent Trimlite


Housings & Trims

For complete fixture, order housing with trim.

6" Vertical Mounted Lamp

P632-EB

- 3 lamps (26w, 32w, 42w), 2 voltages (120V/277), 1 housing
- 120V/277V HPF electronic ballast
- Superior visual cut off of lamp image
- End of Lamp Life Shutdown Circuit Protection
- Ceiling opening 6-7/8", plaster frame 7-7/8" x 10-3/4", Recessed Depth (R.D.) See reflector trims
- Maximum ceiling thickness: 1-1/2"
- Socket cup mounts to trim for consistent lamp positioning
- Socket cup can be positioned in upper or lower positions for different beamspread diameters
- Full reflector design eliminates light leaks around trim flange
- Slotted, interlocking bar hangers securely span 24" T-bar spacing
- UL and CUL listed for damp locations and through wiring
- Integral nailer and T-bar mounting clamp
- Rated for 8 #12 90° conductors (4 in/4 out)



P632-EB

Ceiling Opening: 6-7/8"
 Plaster Frame: 7-7/8" x 10-3/4"
 Recess Depth (R.D.): See trims
 Pryouts: 1/2" and 3/4"

Lamp Wattage	Line Current Voltage	Input Amps	Min Start Watts	Temp.(F)
26W Triple Tube	120	0.25	28	0°
26W Triple Tube	277	0.11	28	0°
32W Triple Tube	120	0.32	36	0°
32W Triple Tube	277	0.14	36	0°
42W Triple Tube	120	0.42	48	0°
42W Triple Tube	277	0.18	48	0°

Total Harmonic Distortion <10%
 Lamp Current Crest Factor <1.5
 Power Factor >.98
 End of Lamp Life Shutdown Circuit Protection

Trims for P632-EB

Lamp: 26w, 32w or 42w triple tube CFL
 RD: 8-1/4", OD: 7-7/16" (except as noted)

Open Trim



P6621-30 White

Scoop Wall Washer



P6623-30 White

Step Baffle



P6625-30 White

Alzak® Multiplier



P6715-21 Clear Alzak®
 RD: 10-5/8"
 OD: 7-3/4"

Regressed Lens



P6691-83
 Wet location listed
 RD: 8-1/4", OD: 7-5/8"

