


SPREAD LIGHTS



P5238-31WB

SPREAD LIGHT

P5238-31WB Black

Cast aluminum construction. Twist off cover for easy relamping. 6-1/2" dia., 13" ht. One 12V halogen bi-pin, 20w max. included. 



P5265-31

DOMES

P5265-31 Black

Cast aluminum construction. White innerlined shade for maximum light output. 9" dia., 26-3/4" ht. One medium base A-19 lamp, 100w max.


LINEAR



P5246-31

LINEAR PATH LIGHT

P5246-31 Black

Linear path light with ground stake. Die cast aluminum construction with louvered glass. Use with P8270-31 transformer. 5-3/8" W., 2-3/8" ht. Extends 4-3/8". One 1.5w LED module included. 


PROGRESS  LED



P5200-20

LINEAR PATH LIGHT

P5200-20 Antique Bronze

Cast solid bronze. Furnished with stake. 7" W., 1-7/8" ht. One 12-volt T5 wedge base, 18w max. included. 

PAGODA



P5204-38



P5204-31



P5219-31


PAGODA


P5204-38 Green

P5204-31 Black
Die-cast aluminum. Clear glass liner. 1/2 NPS threaded fitting for permanent or P5233 for portable installation. Cannot be used with P5312-31. 6" dia., 7-1/8" ht. One medium base lamp, 100w max.

PAGODA

P5219-31 Black

Die-cast aluminum. Clear glass liner. 1/2 NPS threaded fitting for P8667 or P8618 installation. Cannot be used with P5312-31. 6" dia., 7-1/8" ht. One 12V T5 wedge base, 18w max included. 

All low voltage  fixtures include: 1/2 NPS threaded adapter connector (P8651) mounting stake (P8618-31), and lamp except LED fixtures. Must be connected to a 12V transformer, page 748.