

5" INCANDESCENT

HOUSINGS & TRIMS

For complete fixture, order housing with trim.

Standard IC and Non-IC Universal Housings

New Construction Air-Tight IC

New Construction Non-IC

Remodel Non-IC



P85-AT
Ceiling opening: 5-1/4"
Plaster frame: 8-3/8" x 13"
Recessed depth: 7-5/8"
Pryouts: 1/2" & 3/4"

- P85-AT**
- Rated for direct contact with ceiling insulation
 - Trims are Easy-in and push-lock into place
 - Notched mounting frame for easy alignment
 - Slotted, interlocking bar hangers provide solid mounting on 24" centers.
 - P85-AT meets Washington State Energy Code requirements
 - Can be installed in ceilings from 1/2" to 2" thickness



P85-TG
Ceiling opening: 5-1/4"
Plaster frame: 7-7/8" x 10-3/4"
Recessed depth: 7-1/2"
Pryouts: 1/2" & 3/4"

- P85-TG**
- Nail grip bar hangers accommodate 24" on center ceiling joists or T-bars, and have locking feature to secure housing in place
 - Integral T-bar clamps on bar hangers
 - Complete with grounding pigtail
 - UL and CUL Listed for damp locations and through wiring
 - Integral Romex clamps
 - Rated for 8 #12 90° conductors (4 in/4 out)
 - Can be installed in ceilings from 1/2" to 2" thickness



P185-TG
Ceiling opening: 5-1/8"
Recessed depth: 7-1/2"
Pryouts: 1/2"

- P185-TG**
- Locking clips (furnished) permit quick mounting in ceiling
 - Can be installed in ceilings 1/2" to 1"
 - Rated for 4 #12 90° conductors (2 in/2 out)
 - Rated 60° supply wires in end-of-run applications.
 - Trims are easy in and push into place

IC/Non-IC Trims

For insulated and non-insulated ceilings. 6-1/8" outside diameter, except where indicated.



OPEN
P8168-28 White
65w BR30, 50w PAR 30
Long Neck
85w BR30, 75w PAR 30
Long Neck, 60w A19



EYEBALL
P8176-28 White
6-3/8"
75w PAR30 Short Neck



DEEP CONE
P8172-09 Brushed Nickel
65w BR30, 50w PAR30
Short Neck
85w BR30, 75w PAR30
Short Neck



DEEP CONE
P8172-21A Clear Alzak®
P8172-22A Gold Alzak®
White flange
65w BR30, 50w PAR30
Short Neck
85w BR30, 75w PAR30
Short Neck



STEP BAFFLE
P8175-31 Black
P8175-28 White
65w BR 30, 50w PAR 30
Long Neck
65w BR 30, 50w PAR-30
Long Neck, 40w A19



STEP BAFFLE
P8175-20 Antique Bronze
65w BR 30, 50w PAR 30
Long Neck
65w BR 30, 50w PAR-30
Long Neck, 40w A19



OPEN SHOWER TRIM
P8367WL-28 White
Wet location listed
Metal flange
50w PAR 30 Short Neck*



SHOWER LIGHT
P8109-28 White
Wet location listed
Metal flange
40w A19, 50w PAR30
60w A19, 75w PAR30

Lamp wattages shown are maximum. For accessories see page 826.

Patent Pending

** WL trims require use with outdoor rated PAR lamps*