5" SHALLOW CEILINGS

HOUSINGS & TRIMS

For complete fixture, order housing with trim.

Shallow IC and Non-IC Universal Housings

New Construction

Air-Tight IC and Non-IC



P84-AT Ceiling opening: 5-1/4" Plaster frame: 7-7/8" x 10-3/4" Recessed depth: 5-1/4" Pryouts: 1/2" & 3/4"

P84-AT

- Notched mounting frame for easy alignment
- Can be installed in ceilings from 1/2'' to 1-1/2'' thick
- Nail grip bar hangers accommodate up to 24" on center ceiling joists
- Slotted interlocking bar hangers provide solid mounting on 24" centers
- Locking feature to secure housing
- Integral T-bar clamps
- Integral Romex clampsUL & CUL listed for damp locations
- & through wiring
 Rated for 8 #12 90°
- conductors (4 in/4 out)
- Trims are easy-in & push-lock into place
- Shallow profile (5-1/2") for 2x6 construction
- Adjustable lamp position
- Meets Washington State
- Energy Code requirements





P184-TG

Ceiling opening: 5-1/8" Recessed depth: 5-1/2" Pryouts: 1/2"

P184-TG

- Locking clips (furnished) permit quick mounting in ceiling
- Can be installed in ceilings from 1/2" to 1" thick.
- UL & CUL listed for damp locations • Rated for 4 #12 90° conductors
- (2 in/2 out). • Rated for 60° supply wires
- in end-of-run applications. • Trims are easy-in & push-lock
- into place
 Shallow profile (5-1/2") for 2x6 construction

IC/Non-IC Trims

For insulated and non-insulated ceilings. 6-1/8" outside diameter. IC/Non-IC applications.



SHALLOW BAFFLE P8375-28 White P8375-31 Black 65w BR-30, 50w PAR-30



OPEN P8368-28 White 65w BR-30, 50w PAR-30



ALZAK* P8368-21A Clear Alzak* 65w BR-30, 50w PAR-30



EYEBALL P8176-28 White 6-3/8" 75w PAR-30 Short Neck



OPEN SHOWER TRIM P8367-WL28 White Wet location listed 50w PAR 30*

813





ALZAK* P8368-22A Gold Alzak* 65w BR-30, 50w PAR-30



DROP OPAL SHOWER P8109-28 White Wet location listed Metal flange 30w R-20

