

4" INCANDESCENT

HOUSINGS & TRIMS

IC, Air-Tight Housing

New Construction Air-Tight IC



P831-AT

Ceiling opening: 4-1/2"
Plaster frame: 8-3/8" x 13"
Recessed depth: 7-1/2"

P831-AT

- Integral Romex clamp
- Notched plaster frame for easy alignment
- Trim mounted socket snaps into trim for consistent lamp positioning
- UL and CUL listed for damp locations and feed through wiring
- Rated for 8 #12 90° conductors (4 in/4 out)
- Nail grip bar hangers accommodate up to 24" on center ceiling joists
- Integral T-bar clamps
- Locking feature to secure housing
- Adjustable from 1/2" to 2-1/2" ceiling thickness
- Shipped in air-tight configuration
- Meets WSEC code requirements

Non-IC Housings

New Construction Non-IC



P830-TG

Ceiling opening: 4-1/2"
Plaster frame: 7-7/8" x 10-3/4"
Recessed depth: 5-1/2"
Pryouts: 1/2" & 3/4"

P830-TG

- Integral Romex clamp
- Notched plaster frame for easy alignment
- Trim mounted socket snaps into trim for consistent lamp positioning
- UL and CUL listed for damp locations and through wiring
- Rated for 8 #12 90° conductors (4 in/4 out)
- Nail grip bar hangers accommodate up to 24" on center ceiling joists
- Integral T-bar clamps
- Locking feature to secure housing
- Adjustable from 1/2" to 2-1/2" ceiling thickness

Remodel Non-IC



P832-TG

Ceiling opening: 4-1/4"
Recessed depth: 5-1/2"
Pryouts: 1/2"

P832-TG

- Retrofit version of P830-TG for use in existing ceilings
- Integral flange on housing and exclusive locking bars permits quick mounting in ceilings from 1/2" to 1" thick
- Attached junction box with removable sides
- UL and CUL listed for damp locations and through wiring

For complete fixture, order housing with trim.

IC Trims

5" outside diameter. IC trims may be used as Non-IC trims with same wattages. Lamps tilt 20°.



OPEN
P8041-09 Brushed Nickel
50w PAR 20, R20



OPEN
P8041-28 White
50w PAR 20, R20



PINBALL
P8042-28 White
40w PAR 16, 30w R20



WALL WASHER
P8047-31 White with Black Baffle
40w PAR 16, 35w R 20



EYEBALL
P8046-28 White
P8046-09 Brushed Nickel
P8046-20 Antique Bronze
40w PAR 16, 30w R 20



STEP BAFFLE
P8044-31 Black Baffle
P8044-09 Brushed Nickel
P8044-28 White Baffle
55w PAR 16,
50w PAR 20, R20



STEP BAFFLE
P8044-20 Antique Bronze
55w PAR 16,
50w PAR 20, R20



ALZAK® CONE
P8043-22 Gold Alzak®
P8043-21 Clear Alzak®
75w PAR 16,
R 20, 50w PAR 20



ALZAK® CONE
P8048-21 Clear Alzak®
75w PAR 16,
R 20, 50w PAR 20



ALZAK® CONE
P8049-31 Black Alzak®
75w PAR 16,
R 20, 50w PAR 20



OPEN SHOWER TRIM
P8041WL-28 White
Wet location listed
50w PAR 20*

Non-IC Trims

Insulation must be 3" from housing 5" outside diameter. Lamps tilt 20°.



STEP BAFFLE
P8044-09 Brushed Nickel
P8044-20 Antique Bronze
Unpainted flange
55w PAR 16,
50w PAR 20, R 20



STEP BAFFLE
P8044-28 White
P8044-31 Black
55w PAR 16,
50w PAR 20, R 20



WALL WASHER
P8047-31 White with Black Baffle
40w PAR 16,
35w R 20, PAR 20



EYEBALL
P8046-20 Antique Bronze
75w PAR 16, 50w PAR 20



EYEBALL
P8046-09 Brushed Nickel
P8046-28 White
75w PAR 16, 50w PAR 20



OPEN SHOWER TRIM
P8041WL-28 White
Wet location listed
50w PAR 20*



ALZAK® CONE
P8043-21 Clear Alzak®
55w PAR 16,
50w PAR 20, R 20



ALZAK® CONE
P8043-22 Gold Alzak®
55w PAR 16,
50w PAR 20, R 20



PINHOLE SPOT
P8042-28 White
40w PAR 16, 30w R 20