

4" LOW VOLTAGE MR 16

HOUSINGS & TRIMS

For complete fixture, order housing with trim.

Low Voltage Housing

New Construction Air-Tight & IC

New Construction Non-IC

Remodel Non-IC



P817-AT
Ceiling opening: 4-1/2"
Plaster frame: 15-3/4" x 9-3/4"
Recessed depth: 7-1/2"
Pryouts: 1/2" & 3/4"

- P817-AT**
- UL and CUL Listed for damp locations and through wiring
 - Meets Washington State Energy Code requirements
 - Electronic transformer
 - Can be installed in ceilings from 1/2" to 2-1/2" thick
 - Rated for 8 #12 90° conductors (4 in/4 out)



P816-TG
Ceiling opening: 4-1/2"
Plaster frame: 7-7/8" x 10-3/4"
Recessed depth: 5-1/2"
Pryouts: 1/2" & 3/4"

- P816-TG**
- UL and CUL Listed for damp locations and through wiring
 - Rated for 8 #12 90° conductors (4 in/4 out)
 - Can be installed in ceilings from 1/2" to 2-1/2" thick
 - Magnetic transformer



P818-TG
Ceiling opening: 4-1/4"
Recessed depth: 5-1/2"
Pryouts: 1/2"

- P818-TG**
- Integral flange on housing and exclusive locking bars permit quick mounting on ceilings from 1/2" to 1" thick
 - UL & CUL Listed for damp locations
 - Rated for 4 #12 90° conductors (2 in/2 out)
 - Rated for 60° supply wires in end-of-run applications
 - Magnetic transformer

IC Trims & Non-IC Trims

5" outside diameter All trims have 360° positioning Lamps tilt 30° max.



STEP BAFFLE
P8037-28 White Baffle
12V 50w MR-16



STEP BAFFLE
P8037-31 Black Baffle
12V 50w MR-16



STEP BAFFLE
P8037-09 Brushed Nickel
12V 50w MR-16



SLOTTED
P8039-28 White
12V 35w MR-16
12V 50w MR-16



PINHOLE
P8036-28 White
12V 35w MR-16
12V 50w MR-16



WALL WASHER
P8045-31 White with Black Baffle
12V 35w MR-16
12V 50w MR-16



EYEBALL
P8057-28 White
Rotates 360°, tilts 30°
12V 50w MR-16



EYEBALL
P8057-20 Antique Bronze
12V 50w MR-16



ALZAK® CONE
P8056-21 Clear Alzak®
12V 50w MR-16

Lamp wattages shown are maximum. For accessories see page 826 for details.