

Bolt Cutters



Bolt Cutters

- Hardened alloy steel jaws are designed and manufactured to assure the longest possible blade life.
- One-step internal cam mechanism provides the quickest and simplest way to keep the cutting blades precisely aligned.
- Handles and grips designed to allow greater mechanical advantage for crisp, controlled cutting.

Catalog No.	Model No.	Description	Capacity/Metals						Weight	
			Soft (15RC) ¹		Medium (31RC) ²		Hard (42RC) ³		lb.	kg
			in.	mm	in.	mm	in.	mm		
14213	S14	Center Cut	5/16	7.9	1/4	6.4	3/16	4.8	1 1/4	1.00
14218	S18	Center Cut	3/8	9.5	5/16	7.9	1/4	6.4	3 3/8	1.50
14223	S24	Center Cut	7/16	11.0	3/8	9.5	5/16	7.9	5 7/8	2.70
14228	S30	Center Cut	1/2	12.7	7/16	11.0	3/8	9.5	8 7/8	4.00
14233	S36	Center Cut	9/16	14.3	1/2	12.7	7/16	11.0	13 1/2	6.10
14238	S42	Center Cut	11/16	17.5	9/16	14.3	1/2	12.7	18 1/4	8.30

Replacement Heads

Catalog No.	Description	Weight	
		lb.	kg
18363	S14 Head Assembly	7/8	1.0
18368	S18 Head Assembly	1 1/4	1.5
18373	S24 Head Assembly	2 1/4	2.7
18378	S30 Head Assembly	8 7/8	4.0
18383	S36 Head Assembly	13 1/2	6.1
18388	S42 Head Assembly	18 1/4	8.3

Cable Cutters



No. 1380 Cable Cutter

- The Model 1380 Cable Cutter is designed to shear-cut insulated aluminum and copper cable through 1 3/8" diameter and 750 MCM*. Drop-forged, heat-treated, alloy steel jaws shear cable with minimum distortion of internal wires. Fitted with fiberglass-insulated handles and rubber grips.

*Not intended for cutting steel or ACSR cable.

Catalog No.	Model No.	Description	Weight	
			lb.	kg
83350	1380	Aluminum and Copper Cable through 1 3/8" Diameter and 750 MCM	4 1/2	2.0