Cable Trimmers



No. 87 ACSR Cable Trimmer

RIDGID No. 87 ACSR Cable Trimmer for fast, accurate cable splice preparation.

- Trims 85 sizes of ACSR cable from 8 AWG to 1,780,000 circular mils (C.M.).
- Bushings for 9 popular cable sizes from 1/0 AWG through 1,780,000 C.M. available from stock.
- The operation of the tool is similar to that of a conventional tubing cutter.
- The bushing holder, cutter and handy carrying case are sold as one unit.
- Case contains storage sockets for 11 bushings. Twelfth bushing is stored in holder.

Catalog	Model No.	Description		Weight	
No.				kg	
54135	87	ACSR Cable Trimmer, includes Bushing Holder, Cutter, and Carrying Case	91/2	4.30	
54270	E-4695	Cutter Wheel	1	0.02	

Catalog No.	Bushing No.	A.W.G. or C.M.	No. of Strands
54440	E-5761	2/0	6/1
54445	E-5762	2/0	6/1
54450	E-5763	4/0	6/1
54465	E-5766	266,800	26/7
54480	E-5769	336,400	26/7
54500	E-5773	397,500	26/7
54520	E-5777	477,000	26/7
54540	E-5781	556,500	26/7
54575	E-5788	636,000	54/7 24/7

Conduit Benders



Heavy-Wall Conduit Benders

- Designed for the larger sizes of heavy-wall conduit. This bender has hardened teeth for slip-resistant grip.
- Extra-long supporting socket minimizes handle breakage.
- Notch in radius protects conduit threads.

Catalan Na	Model No.	Capacity		Weight	
Catalog No.	wodel No.	in.	mm	lb.	kg
35230	B-1709	1/2	12	25/8	1.20
35235	B-1711	1/2 -3/4	12 - 19	23/4	1.30
35240	B-1712	1 - 1 ¹ / ₄	25 - 32	73/4	3.50

Handles not included



Thin-Wall Conduit Benders

- Made of cast iron, these tools have exceptionally smooth side walls which grip conduit snugly to minimize distortion.
- Bending grooves conform to Standard Code Radii. Marks indicate 30°,45°, 60° and 90° bends.

Catalog	Model	Description		Weight	
No.	No.			kg	
35215	B-1677	Bends 1/2" (12 mm) Thin-Wall Conduit to 4" (100 mm) Inside Radius	21/2	1.1	
35220	B-1678	Bends $^3/_4$ " (19 mm) Thin-Wall and $^1/_2$ " (12 mm) Heavy-Wall Conduit to 5" (127 mm) Inside Radius	41/2	2.0	
35225	B-1679	Bends 1" (25 mm) Thin-Wall and 3/4" (19 mm) Heavy-Wall Conduit to 6 1/2" (165 mm) Inside Radius	81/2	3.9	

Handles not included