

Reels & Cameras



SeeSnake® Standard Camera

RIDGID® SeeSnake video inspection systems offer unmatched reliability and performance in a ruggedized package. Each system offers:

- 100% hardened stainless steel camera head spring assembly for optimum durability.
- Rugged, high-intensity lights for exceptional viewing and long life.
- Flexible transmitters make locating easy and are compatible with RIDGID locators.
- Can be used with any SeeSnake monitor or recorder.
- 2" to 12" (5 - 30 cm) Lines up to 325' (99 m).
- Wide pipe diameter capacity range makes this system ideal for a wide range of inspection needs.

Specifications

- Line Capacity – 2" - 12" (5-30cm).
- Maximum Run – 325' (99m).
- Sonde – 512 Hz.
- Weight – 53 lbs / 19.5 kg.
- Reel Frame Diameter – 32" / 81 cm.
- Camera Diameter – 1.365" / 35 mm.
- Camera Length – 1.68" / 42 mm.
- Push Cable Diameter – .44" / 11 mm.
- Operating Temperature – -4° to 104°F / -20° to 40°C.
- Waterproof Depth – 330' / 100 m.
- Video Resolution – 768(H) x 494(V).

Catalog No.	Description	Voltage	Weight	
		V	lb.	kg
14053	200' Color Reel (NTSC)	115	42.0	19.0
14058	325' Color Reel (NTSC)	115	53.0	24.0

Accessories

Catalog No.	Description	Weight	
		lb.	kg
14078	Color Camera Head – NTSC (115V)	-	-
15323	SeeSnake Flexible In-Line Transmitter	0.6	0.3
17563	Color Spanner Wrench	-	-
31753	Count Plus Cable Counter	-	-
64497	SeeSnake 3" (75 mm) Centering Star Guides, Pkg of 20	-	-
64502	SeeSnake 6" (150 mm) Centering Star Guides, Pkg of 10	-	-
64627	SeeSnake Interconnect Cord – 33/10' (10 m / 3m)*	-	-
93387	SeeSnake Guide Hoop, Pkg of 4	-	-
97832	SeeSnake 3" (75 mm) Roller Dolly	-	-
97852	SS Ball Guides Pkg of 10	-	-

Replacement Parts

Catalog No.	Description
12248	18" System Cable with Dubbing Block
14028	Color Self-Leveling Camera Head – NTSC (115V)
14033	Color Self-Leveling Camera Head – PAL (230V)
35103	200' SeeSnake Push Cable Assembly (Single Safety Cable)
35108	325' SeeSnake Push Cable Assembly (Single Safety Cable)