Drum Machines



K-7500 Drum Machine

For 3" to 10" (75-250mm) Lines.

- Recommend 5/8" (16 mm) cable for 3" (75 mm) to 6" (150 mm) drain lines up to 250' (76 m).
- Recommend ³/₄" (20 mm) cable for 4" (110 mm) to 10" (250 mm) drain lines up to 250' (76 m).
- The performance, cable control, durability, and maneuverability demanded by professional users. Ideal for any tough job, such as roots – up to 250' (76 m).
- Cable spins at 200 RPM.
- Powerful, yet quiet, 600W universal motor and gearbox bear down as cutter engages tough obstructions.
- Provides audible and visual signals to operator.
- Inner-drum and ball bearing distributor arm work with motor/gearbox system to reduce chance of cable flip-over inside the drum.
- Main and inner drums won't rust, split or dent ever, and clean easily for professional appearance. Main drum holds up to 100' (30.5 m) of ³/₄" (20 mm) cable or 125' (38 m) of ⁵/₈" (16 mm) cable.
- Powerful AUTOFEED® mechanism has grease fittings and an open design for easy maintenance; advances and retrieves cable up to 22' (6.7 m) per minute.
- Two position stair climber eases transport and loading eliminates extra cost for loading wheels.
- Narrow profile allows machine to fit through bathroom doors.
- Handles adjust to desired height to ensure balanced transport.
- Includes RIDGID® PVC drain cleaning gloves and operator's manual.
- Approved by CSA to CSA and UL Standards (115 V only).

Standard Equipment

- 59360 Tool Box.
- $69250 \frac{3}{16}$ " Hex Wrench.
- 70032 RIDGID PVC Drain Cleaning Gloves.
- 92485 P-Trap Cutter, 3" (75 mm).
- 92495 Spade Cutter, 13/4" (45 mm).
- 92500 Retrieving Auger 29/16" (65 mm).
- 92505 Sawtooth Cutter, 3" (75 mm).
- 92510 Double Cutter, 2" (50 mm).
- 92520 Double Cutter, 3" (75 mm).
- 92560 3/4" (20 mm) x 2' (50 mm) Leader.
- 92830 4" Double Cutter (Blade Only).
- 92855 6" Double Cutter (Blade Only).

Machine Options

Catalog No.	Model No.	Description	Voltage	Weight	
			٧	lb.	kg
59562	K-7500	Machine w/3/4" Pigtail and Standard Accessories	115	150	86.2
60052	K-7500 C-100	Machine, Standard Accessories, and ³ / ₄ " x 100' Inner Core Cable.	115	272	123.7
60062	K-7500 w/C-75	Machine, Standard Accessories, and 3/4" x 75' Inner Core Cable.	115	244	110.9
61102	K-7500	Machine w/5/8" Pigtail and Standard Accessories	115	149	67.8
61512	K-7500 w/C-24	Machine, Standard Accessories, and 5/8" (16 mm) x 100' (30,5 m) Inner Core Cable	220	233	106.0
61517	K-7500 w/C-100	Machine, Standard Accessories, and ³ / ₄ " (20 mm) x 100' (30,5 m) Inner Core Cable	220	272	123.7
61522	K-7500	Machine w/5/8" (16 mm) Pigtail and Standard Accessories	220	149	67.8
61542	K-7500	Machine w/3/4" (20 mm) Pigtail and Standard Accessories	220	150	86.2