

SANICONDENS[®]

Discharge: Vertically to 15 ft. (4.6m) and/or Horizontally to 150 ft. (50m)

Discharge rate at 15': 30 gal/hour (114 Lit./hour)

Discharge rate at 3': 86 gal/hour (326 Lit./hour)

Discharge pipe diameter: 3/8" vinyl tubing

HP: 1/30 HP

Max. Amperage: 1.5 A

Operating Temperature: 95°F (35°C) Maximum 160°F (70°C)


Dimensions: H 6 5/8" (17cm) x W 9 1/2" (24.2cm) x D 5 5/8" (14.3cm)



Part# 040

FEATURES

- 3-Year Warranty
- 2 Inlets for multiple installations
- Includes 20 ft. of kink-free 3/8" tubing
- Standard External Safety Switch
- CSA Listed
- Quiet operation (<45 dBA)



SANIFLO[®]
 A Group SFA Company
 Toll Free: 1-800-571-8191

Please check out our facebook page
 at www.facebook.com/SANIFLO



Copyright 2011 SFA SANIFLO, Inc. All rights reserved

SANIFLO[®]

sanicondens



www.saniflo.com

SANICONDENS®

What Makes This System The Best Choice For Removing Condensate Water?

SK5 MOTOR TECHNOLOGY

Designed for tougher environments and high temperature applications.

COOLING MOTOR DESIGN

Cooling fan increases the life expectancy of the pump as it cools the motor for better efficiency.

INLET ADAPTER

Proper fitting for use with different diameter pipes.

INTEGRATED MOUNTING BRACKETS

Includes hardware kit for quick and easy installation.

THERMAL OVERLOAD

Motor protection

QUARTER TURN (1/4) CHECK VALVE

Eases the removal of the check valve eliminating water spills.

EXTERNAL OVERFLOW SAFETY SWITCH

This auxiliary system will shut down the appliance in the event of pump overflow. The pump comes ready to be wired with simple connections to an audible and/or visual alarm.



EASY TO INSTALL DISCHARGE CONNECTION

Adapter eases the installation to the discharge pipe! (3/8" barbed x 3/4" male end connection)