

Job Name:	Item Number:	
Specifier Name:	Sales Agency:	
Specifier Contact:	Agency Contact:	
Fixture Type:	Comments:	
Quantity:	Approval:	

12V 4" High Ouput LED Module 3000K







L: 4" W: 7/8" H: 5/8"

Description

The miniature, high output LED modules can be used with 12 volt Ambiance Lx Cable Systems powered by magnetic low-voltage or **zero-load** electronic low-voltage transformers. Ambiance High Output LED Modules are dimmable on magnetic and electronic low voltage systems. For magnetic systems, a magnetic low voltage (MLV) dimmer should be used. For electronic, an electronic low voltage (ELV) dimmer is recommended.

Specifications

98703S-986				
Tinted Aluminum				
L: 4" W: 7/8" H: 5/8"				
5" on center				
Acrylic - Frosted				
12V				
3000°K				
170				
3 watts				
56.7 lm/w				
>85 CRI				
50,000 hours to 70%				
cETL Listed for Damp Locations				
5-Year Limited Warranty				

Instruction Sheets

• Trilingual (English, Spanish, and French) (990LXLEDMOD)

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	UPS Ship
Individual	98703S-986	1	785652218644	4.4	1.2	1.2	0.004	0.1	Yes
Master Pack	98703S-986	5	10785652218641	5.25	1.25	4.5	0.017	0.5	Yes
Shipping Master		200	20785652218648	12.5	9.25	11	0.736	19.4	Yes

Component Diagram:





7400 Linder Ave. | Skokie, Illinois 60077 | 800-347-5483 © 2013 Sea Gull Lighting LLC, a Generation Brands Company.