


1 CHOOSE A LAMP & LAMPHOLDER

LED FESTOON

Upgrade to our Ambiance Lx LED Festoons from our 5w Xenon Festoons and realize an energy savings of over 80% without compromising light output. Lx LED Festoons snap into Lx Festoon Lampholders (sold separately), making retrofitting of existing systems easy. For new systems, pick a matching Lx Festoon Lampholder and clip them onto your Lx Cable and Track. Lx LED Festoons are available in 2700, 3000, and 4000K, in both 12 and 24v.



NOTE: Lamps in chart below only compatible with Festoon Lampholder 9830 and Festoon Adjustable Lampholder 94323 (page 49).

ITEM NUMBER	96116S(-xx)	96117S(-xx)	96118S(-xx)	96120S(-xx)	96119S(-xx)	96121S(-xx)
FINISH	(-32) Clear and (-33) Frosted					
COLOR TEMPERATURE	2700K		3000K		4000K	
VOLTAGE	12v AC	24v AC	12v AC	24v AC	12v AC	24v AC
DELIVERED LUMENS	59		60		62	
POWER CONSUMPTION	.708w		.708w		.708w	
EFFICACY	83 lm/w		85 lm/w		88 lm/w	
COLOR RENDERING INDEX	>90 CRI		>90 CRI		>85 CRI	
RATED AVERAGE LIFE	50,000 hours to 70%					
DIMMABLE ⁽¹⁾	Down to 10%					
LAMP BASE	Festoon					
RECOMMENDED SPACING	4" on center (1" minimum separation)					
CERTIFICATION	cETL, damp rated					

⁽¹⁾ Ambiance Lx LED Festoons are dimmable on magnetic and electronic low voltage systems. For magnetic systems, a standard incandescent or magnetic low voltage (MLV) dimmer can be used. For electronic, an electronic low voltage (ELV) dimmer is recommended. See pg. 108 for more on dimming.

See Ambiance-Lighting.com for additional photometric data.