

2 SELECT CABLE

Spools of cable specially designed with easy piercing, self-sealing insulation over stranded copper wire for use with Ambiance Lx Cable Lighting System. Markings for lampholder placement every 2". Designed to be mounted in Ambiance Lx Track.



INDOOR 25' SPOOL⁽¹⁾

9469-12, black finish
9469-15, white finish

L: 25' W: 0.375" H: 0.187"

INDOOR 500' SPOOL⁽¹⁾

9472-12, black finish
9472-15, white finish

L: 500' W: .375" H: .187"

INDOOR 50' SPOOL⁽¹⁾

9470-12, black finish
9470-15, white finish

L: 50' W: .375" H: .187"

INDOOR 1000' SPOOL⁽¹⁾

9473-12, black finish
9473-15, white finish

L: 1000' W: .375" H: .187"

INDOOR 100' SPOOL⁽¹⁾

9471-12, black finish
9471-15, white finish

L: 100' W: .375" H: .187"

⁽¹⁾ Lx 10/2 AWG 105° C cable is rated for indoor use only. Maximum wattage per length 300w at 12v; 600w at 24v cable is not rated to run behind walls. Check with local codes.

3 SELECT TRACK

TRACK

Noryl[®] track to support cable and lampholders. Use double faced tape (**9450**), track clip (**9438**) or screws (**9862**) through pre-drilled holes to attach track to surface. Track may be flexed, notched, curved and easily cut for various applications.

9435-12, black finish
9435-15, white finish

L: 48" W: .5" H: .25"



TRACK WITH FASCIA PANEL

One piece Noryl[®] fascia panel with integral track to support cable and lampholders. Use under shelves or where system cannot be hidden behind a lip on cabinets. Track/fascia may be easily cut to various lengths. Use double faced tape (**9450**) track clip (**9438**) or screws (**9862**) through pre-drilled holes to attach track/fascia to surface. Use double-faced tape on glass and other smooth surfaces.

9443-12, black finish
9443-15, white finish

L: 48" W: .875" H: 1.125"

