



SIEMENS LOW VOLTAGE ES SERIES LOAD CENTER. FACTORY INSTALLED MAIN BREAKER WITH 24 1-INCH SPACES ALLOWING MAX 42 CIRCUITS. 3-PHASE 4-WIRE SYSTEM RATED 120/240V OR 120/208V (150A) 10KA INTERRUPT. SPECIAL FEATURES: ALUMINUM BUS, GRAY TRIM, NEMA TYPE1 ENCLOSURE FOR INDOOR USE.

|                              |             |
|------------------------------|-------------|
| Configuration of the busbars | 150A        |
| Mounting type                | Combination |
| Phase number                 | 3           |
| Suitability for operation    | Residential |

### Electricity

|  |       |
|--|-------|
| Ampacity   | 150 A |
| Voltage between phase and Ground (GND) rated value | 120 V |
| Voltage between phase and phase rated value        | 240 V |

### Switching capacity

|   |         |
|---|---------|
| Switching capacity current acc. to EN 60898 rated value | 22000 A |
|---|---------|

### Model

|                        |              |
|------------------------|--------------|
| Product brand name     | Siemens      |
| Product sub brand name | Load Centers |

### Mechanical Design

|  |    |
|--|----|
| Number of width units for installation width | 24 |
|--|----|