CATALOG NUMBER

ECLX071M



Ground Bar Kit

Same As:

- LX071M
- LX071MU

GROUND BAR INSTALLATION INSTRUCTIONS




DANGER

Hazardous Voltage.
Will cause death, serious injury or substantial property damage.

Turn off power supplying this equipment before working inside.

Note: This instruction outlines the recommended installation procedure.



▲ SAFETY INSTRUCTIONS

APPROXIMATE LOCATION* OF EQPT. GROUND BAR MTG. HOLES (2" CENTERS) WITHIN ENCLOSURE.

*NOTE: MAY VARY FROM ONE TO TWO PER DEVICE. "A" OR "D" MOST LIKELY OCCUR IN SMALL ENCLOSURES. "B" AND "C" COMBINATION ARE MORE TYPICAL.

REMOVE SCREWS, POSITION HOLES IN BRACKET OVER MTG. HOLES IN PANEL BACKWALL AND FASTEN DOWN

IN SOME COMBINATION DEVICES, SCREWS ARE PROVIDED WITH DEVICE. IN THESE CASES, DISCARD SCREWS SUPPLIED WITH GROUNDING BAR, AND USE #8 SCREWS PROVIDED WITH DEVICE.

SEE WIRING DIAGRAM FOR WIRE RANGE SIZE AND TIGHTENING TORQUE REQUIREMENTS.

© 2004 Copyright Siemens Energy & Automation, Inc.

GRD BAB

BRACKET

4810413 Rev.A

MTG SCREWS

TORQUE TO 24-30 LB-IN