

## CERTIFIED LEAD FREE - MODELS 800LF - 818LF 800LF Series Deluxe Frost-Proof Yard Hydrant



- 3/4" or 1" NPT Female Inlet
- 3/4" Male Hose Thread Outlet
- Cast Iron Head and Handle with Blue Polyester Powder Coated Finish.
- Max. Pressure 120 PSI
- Many Parts and Accessories are common for all Models.
- Yard hydrant accessories...See page 27.





Certified by Truesdail Laboratories. Meets all Federal and state Safe Drinking Water Acts and requirements. **Does not meet California Prop. 65 (Environmental Law)**

3/4" Inlet Part No.	1" Inlet Part No.	Bury Depth	Weight Each lbs.
800LF	810LF	1	11.9
801LF	811LF	1 1/2	13.5
802LF	812LF	2	14.5
803LF	813LF	3	16.8
804LF	814LF	4	18.9
805LF	815LF	5	21.2
806LF	816LF	6	23.4
807LF	817LF	7	25.7
808LF	818LF	8	28.2

**All Simmons Yard Hydrants are Individually Boxed.**

### Flow Rates:

(For All Simmons Yard Hydrant Models except 6800 Series)



### Parts Kit



### CERTIFIED LEAD FREE 800LF Series Yard Hydrant Parts

Ref. No.	Name of Part
850SB	Parts Kit
840	Head Complete
<b>A</b>	8820 Head
<b>B</b>	8821 Handle
<b>C</b>	8822SB Valve Body (3/4") 8832A Valve Body (1")
<b>D</b>	8845 Extension Rod, 7/16"
<b>E</b>	8824* Flow Lock Wheel
<b>F</b>	8825• Brass Connector
<b>G</b>	8826• Brass Links (Price per Pair)
<b>H</b>	8847• Brass Packing Nut
<b>I</b>	8844 Hose Adapter
<b>J</b>	8829* Brass Stem, Square Head
<b>K</b>	8839• Buna-N "O" Rings (Price per Pair)
<b>L</b>	8814 Pump Rod, 7/16"
<b>M</b>	8815 Galvanized Pipe Casing, 1"
<b>N</b>	8842• Plunger (One Piece)
<b>P</b>	8834 Rod Coupling, 7/16"
<b>Q</b>	8301• Stainless Steel Lock Nut
<b>R</b>	8836• Fulcrum Bolt Stainless Steel
<b>S</b>	8837• Square Head Set Screw Stainless
<b>T</b>	8610* Screw for Flow Lock Wheel

\*Included in Parts Kit. Refer to Parts Kit photo at left.  
\*These parts make up the flow lock wheel assembly.

**MADE IN U.S.A.**



## CERTIFIED LEAD FREE 4800LF Series Premier Frost-Proof Yard Hydrant


- 3/4" NPT Female Inlet
- 3/4" Male Hose Thread Outlet
- All components are identical to 800LF Series except head casting and handle are smaller. Does not have flow lock wheel.
- Polyester powder coated finish.
- Max. Pressure: 120 PSI
- Individually boxed.
- Refer to 3/4" Flow Rate Chart...Page 23.
- Yard hydrant accessories... See page 27.

Part No.	Bury Depth	Weight Each lbs.
4800LF	1	11.2
4801LF	1 1/2	12.6
4802LF	2	13.6
4803LF	3	15.9
4804LF	4	18.1
4805LF	5	20.6
4806LF	6	23.0
4807LF	7	25.4
4808LF	8	27.8



Certified by Truesdail Laboratories. Meets all Federal and state Safe Drinking Water Acts and requirements. **Does not meet California Prop. 65 (Environmental Law)**

NSF/ANSI 372



### CERTIFIED LEAD FREE 4800LF Series Yard Hydrant Parts

Part Ref. No.	Name of Part
850SB	Parts Kit
890	Head Complete
<b>V</b> 8891	Head
<b>W</b> 8892	Handle
<b>C</b> 8822SB	Valve Body
<b>D</b> 8843	Extension Rod 7/16"
<b>F</b> 8825•	Brass Connector
<b>G</b> 8826•	Brass Links (Price per Pair)
<b>H</b> 8847•	Brass Packing Nut
<b>I</b> 8844	Hose Adapter
<b>K</b> 8839•	Buna-N "O" Rings (Price per Pair)
<b>L</b> 8814	Pump Rod, 7/16"
<b>M</b> 8815	Galvanized Pipe Casing, 1"
<b>N</b> 8842•	Plunger (One Piece)
<b>P</b> 8834	Rod Coupling, 7/16"
<b>Q</b> 8301•	Stainless Steel Lock Nut
<b>R</b> 8836•	Fulcrum Bolt Stainless Steel
<b>S</b> 8837•	Square Head Set Screw Stainless

•Included in Parts Kit.



**Simmons  
Superior  
Packaging**



**Parts Kit**

MADE IN U.S.A.