



NSF/ANSI 372

CERTIFIED LEAD FREE Single Tap

- Silicon bronze cast body.
- Silicon bronze cast poppet.
- Female threads.



NSF/ANSI 372

CERTIFIED LEAD FREE Double Tapped

- Silicon bronze cast body.
- Silicon bronze cast poppet.
- Female threads.

Control Center



NSF/ANSI 372

CERTIFIED LEAD FREE Check Valve

- Silicon bronze cast body.
- Silicon bronze cast poppet.
- Four tappings. • Female threads.



601-604 tappings:
One 1/8" inlet,
Two 1/4" outlets,
One 1/8" outlet.

606-607 tappings: Two 1/4" outlets.

Part No. Stemmed	Part No. Stemless	Size	Tapped		Wt.Ea. lbs.	Carton Quantity
			Inlet	Outlet		
521SB	-	3/4	1/8		.8	1
550SB	-	3/4	1/4		.8	1
551SB	-	3/4		1/8	.8	1
552SB	-	3/4		1/4	.8	1
522SB	2522SB	1	1/8		1.2	1
553SB	2553SB	1	1/4		1.2	1
554SB	2554SB	1		1/8	1.2	1
555SB	2555SB	1		1/4	1.2	1
523SB	2523SB	1 1/4	1/8		1.7	1
556SB	2556SB	1 1/4	1/4		1.7	1
558SB	2558SB	1 1/4		1/4	1.7	1
524SB	2524SB	1 1/2	1/8		2.0	1
559SB	2559SB	1 1/2	1/4		2.0	1
560SB	2560SB	1 1/2		1/8	2.0	1
561SB	2561SB	1 1/2		1/4	2.0	1
525SB	2525SB	2	1/8		3.7	1
562SB	2562SB	2	1/4		3.7	1
563SB	2563SB	2		1/8	3.7	1
564SB	2564SB	2		1/4	3.7	1
526SB	-	2 1/2	1/8		9.8	1
527SB	-	3	1/8		10.1	1
528SB	-	4	1/8		23.5	1

Part No. Stemmed	Part No. Stemless	Size	Tapped		Wt.Ea. lbs.	Carton Quantity
			Inlet	Outlet		
541SB	-	3/4	1/8	1/4	.8	1
580SB	-	3/4	1/4	1/4	.8	1
542SB	2542SB	1	1/8	1/4	1.2	1
581SB	2581SB	1	1/4	1/4	1.2	1
588SB	2588SB	1	1/8	1/8	1.2	1
543SB	2543SB	1 1/4	1/8	1/4	1.7	1
582SB	2582SB	1 1/4	1/4	1/4	1.7	1
589SB	2589SB	1 1/4	1/8	1/8	1.7	1
544SB	2544SB	1 1/2	1/8	1/4	2.0	1
583SB	2583SB	1 1/2	1/4	1/4	2.0	1
533SB	2533SB	1 1/2	1/8	1/8	2.0	1
545SB	2545SB	2	1/8	1/4	3.7	1
584SB	2584SB	2	1/4	1/4	3.7	1
546SB	-	2 1/2	1/8	1/4	9.8	1
547SB	-	3	1/8	1/4	10.1	1
548SB	-	4	1/8	1/4	23.5	1

Part No.	Size	Wt. Ea. lbs.	Carton Quantity
601SB	1	1.3	1
602SB	1 1/4	1.7	1
603SB	1 1/2	2.1	1
604SB	2	3.6	1
606SB	1	1.3	1
607SB	1 1/4	1.7	1

*Silicon bronze components contain less than .05% (1/20 of 1%) Lead.

Check Valves furnished with Buna-N O-Ring, stainless steel spring, stainless steel washer, and stainless steel locknut.
All valves 3/4" through 1-1/2" have a working pressure of 400 psi. All valves 2" and larger have a working pressure of 600 psi.
190° Maximum Temperature Rating

MADE IN U.S.A.