

Check Valve – 500 SB Series



Check Valve – 500 SB Series

Certified Lead Free*

- Silicon bronze cast body
- Silicon bronze cast poppet
- Female Threads

* Silicon bronze components contain less than .05% (1/20 of 1%) Lead

All check valves furnished with Buna-N O-Ring, stainless steel spring, stainless steel washer and stainless steel locknut.

All valves 3/4" through 1-1/2" have a working pressure of 400 psi. All valves 2" and larger have a working pressure of 600 psi.

Part No.	Size	Weight	List Price
501SB	1/2 in.	.60	\$39.77
502SB	3/4 in.	.80	\$40.26
503SB	1 in.	1.1	\$42.39
513SB*	1 in.	1.2	\$44.22
504SB	1 1/4 in.	1.6	\$58.10
514SB**	1 1/4 in.	1.7	\$62.09
505SB	1 1/2 in.	2.1	\$81.21
506SB	2 in.	3.7	\$131.37
507SB	2 1/2 in.	9.8	\$560.63
508SB	3 in.	10.8	\$675.66
509SB	4 in.	23.6	\$1174.60
510SB***	5 in.	25.1	\$1579.58
511SB	6 in.	41.5	\$2146.64

* Has Longer Threads

** Has Longer Threads

*** Has 5" male threads on both ends