

Check Valve – Double Tap



Check Valve – Double Tap

Lead Free*

- Silicon bronze cast body
- Silicon bronze cast poppet
- Female Threads

* Silicon bronze components contain less than .05% (1/20 of 1%) Lead

All check valves furnished with Buna-N O-Ring, stainless steel spring, stainless steel washer and stainless steel locknut.

All valves 3/4" through 1-1/2" have a working pressure of 400 psi. All valves 2" and larger have a working pressure of 600 psi.

Part No.	Part No.	Size	Tapped		Weight	List Price	List Price
Stemmed	Stemless		Inlet	Outlet		Stemmed	Stemless
541SB	-	3/4	1/8	1/4	.8	\$48.35	-
580SB	-	3/4	1/4	1/4	.8	\$48.35	-
542SB	2542SB	1	1/8	1/4	1.2	\$58.06	\$58.06
581SB	2581SB	1	1/4	1/4	1.2	\$58.06	\$58.06
588SB	2588SB	1	1/8	1/8	1.2	\$58.06	\$58.06
543SB	2543SB	1 1/4	1/8	1/4	1.7	\$71.43	\$71.43
582SB	2582SB	1 1/4	1/4	1/4	1.7	\$71.43	\$71.43
589SB	2589SB	1 1/4	1/8	1/8	1.7	\$71.43	\$71.43
Part No.	Part No.	Size	Tapped		Weight	List Price	List Price
Stemmed	Stemless		Inlet	Outlet		Stemmed	Stemless
544SB	2544SB	1 1/2	1/8	1/4	2.0	\$92.52	\$92.52
583SB	2583SB	1 1/2	1/4	1/4	2.0	\$92.52	\$92.52
533SB	2533SB	1 1/2	1/8	1/8	2.0	\$92.52	\$92.52
545SB	2545SB	2	1/8	1/4	3.7	\$143.41	\$143.41
584SB	2584SB	2	1/4	1/4	3.7	\$143.41	\$143.41
546SB	-	2 1/2	1/8	1/4	9.8	\$700.63	-
547SB	-	3	1/8	1/4	10.1	\$989.29	-
548SB	-	4	1/8	1/4	23.5	\$1293.67	-