

## TKO™

### Total Knockout Closet Flange

Patent #5,377,361



886-4PT

- PVC and ABS, 3" spigot, 3" hub, 3" Sch. 30 hub, 4" spigot, 4" hub
- Over ten years of proven performance
- Knockout will not break apart and cannot fall down drain pipe
- Strong, corrosion-resistant stainless steel ring eliminates cracked flanges
- Easier installation, no need to hold knockout while hammering
- Holds five floors (22 PSI) for head test



884-PTM

## Push-Tite™

### Gasketed Closet Flange



887-GPTM



888-GPM

- PVC and ABS, 3" and 4" inside fit
- Gasket seals inside DWV pipe
- Engineered elastomer gasket is chemical and heat resistant

## Full Flush™

### Offset Closet Flange



889-POM

- Full-flow, 3" I.D. throat
- Also available in a TKO version
- Allows for 1½" offset in any direction for closet bowl setting
- Solvent welds over 3" or inside 4" Sch. 40 PVC or ABS DWV

## Brass Closet Flange Ring



890-4BPK



890-4BDPK

- Solid brass
- For use with lead pipe
- Deep seal model provides more surface area for better joint

## Drop-Kick™

### 45° Offset Closet Flange



889-45PM

- Full-flow, 3" I.D. throat—no restriction
- Solvent welds inside 3" Sch. 40 PVC or ABS fitting hub
- Corrosion-resistant stainless steel swivel ring is engineered for maximum strength

## Ringer™

### Stainless Steel Closet Ring



886-MR

- Stainless steel ring is corrosion resistant
- Perfect for repairs to damaged closet flanges, or new concrete floor installations
- Fits securely over damaged flanges

## Raise-A-Ring™

### Closet Flange Extension Ring



886-R



886-RQ

- Can be stacked if needed
- Build up existing flange when added subfloor, tile, etc. leaves flange at or below floor level
- 886-R is 7/16" thick
- 886-RQ is 1/4" thick