


Regal[®] 186-0.5 XL Flushometer



- ▶ **Description**
Exposed Urinal Flushometer, for 3/4" top spud urinals.
- ▶ **Flush Cycle**
□ Model 186-0.5 High Efficiency (0.5 gpf/1.9 Lpf)
- ▶ **Specifications**
Quiet, Exposed, Diaphragm Type, Chrome Plated Urinal Flushometer with the following features:
 - ADA Compliant Metal Oscillating Non-Hold-Open Handle
 - 3/4" I.P.S. Screwdriver Bak-Chek[®] Angle Stop
 - Vandal Resistant Stop Cap
 - Sweat Solder Adapter with Cover Tube
 - Cast Set Screw Wall Flange
 - Adjustable Tailpiece
 - Cast Wall Flange with Set Screw
 - Vacuum Breaker Flush Connection
 - Spud Coupling and Spud Flange for 3/4" Top Spud
 - High Copper, Low Zinc Brass Castings for Dezincification Resistance
 - Non-Hold-Open Handle and No External Volume Adjustment to Ensure Water Conservation
 - Low Consumption flush accuracy controlled by Para-Flo[™] Technology
 - Handle Packing, Stop Seat and Vacuum Breaker to be Molded from PERMEX[®] Rubber Compound for Chloramine Resistance

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037.

- ▶ **Accessories**
See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.
- ▶ **Fixtures**
Consult Sloan for Sloan brand matching fixtures.



Sloan Valve Company is buying renewable energy certificates to meet 100% of the company's purchased electricity use at its Franklin Park, Illinois facility.

This space for Architect/Engineer approval

The information contained in this document is subject to change without notice.