



Main

| | |
|-----------------------|---|
| Product | Miniature circuit-breaker |
| Range | QO |
| Line Rated Current | 20 A |
| System Voltage | 120 V AC 120/240 V AC 240 V AC 48 V DC |
| Mounting Type | Plug-in |
| Number of Poles | 3P |
| Circuit Breaker Type | Standard |
| Ratings | HACR rated |
| Electrical Connection | Pressure plate |

Complementary

| | |
|------------------------|---|
| Interrupt Rating | 5 kA at: 48 V DC 10 kA at: 120/240 V AC 50/60 Hz 10 kA at: 240 V AC 50/60 Hz 10 kA at: 120 V AC 50/60 Hz |
| Number of Panel Spaces | 3 |
| Wire Size | AWG 14...AWG 8 (copper or aluminium) |
| Height | 3 in |
| Depth | 2.91 in |
| Width | 2.25 in |

Environment

| | |
|----------------|------------------|
| Certifications | CSA UL listed |
| Ambient Rating | 104 °F (40 °C) |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1323 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference contains SVHC above the threshold - Go to CaP for more details Go to CaP for more details |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|