

Stab-lok Circuit Breakers

General Information

Features and Benefits

Breaker Features:

- Type NC with Robertson/slot screws
- Type NC with colour coded handles
- Thermal magnetic trip protection
- Exclusive line side stab connection
- Trip free operation
- Calibrated at 40° C
- Availability of a wide range of GFCIs
- Arc resistant case

NC The Compact Stab-lok Breaker -
1/2" Wide per pole



NC015, NC0215, NC0230

Stab-lok Breaker Rating Table

Type	Poles	Amp Rating	Maximum Voltage	Interrupting Capacity
NC	1	15-50	120	10,000 A
	2	15-50	120/240	10,000 A
NA	1	15-50	120	10,000 A
	2	15-150	120/240	10,000 A
	3	15-100	240	10,000 A
1C	2	30-40	120/240	10,000 A
		50-125		22,000 A
2C	2	100-200	120/240	22,000 A

NA The Original Stab-lok Breaker - 1" Wide per pole



NA15



NA215



NA3P20



NA2P100

Stab-lok Circuit Breakers Circuit Breakers and Accessories

Standard and Main Circuit Breakers

DE1 LOAD CENTRES

Standard Loadcentre Breakers

Type	Amp Rating	1 Pole Cat. No.	List Price	Lug Range	2 Pole Cat. No.	List Price	Lug Range	3 Pole Cat. No.	List Price	Lug Range
NC	15	NC015		#14 - #6	NC0215		#14 - #6	—	—	—
	20	NC020			NC0220			—	—	
	25	NC025			NC0225			—	—	
	30	NC030			NC0230			—	—	
	40	NC040			NC0240			—	—	
	50	NC050		#14 - #4	NC0250		#14 - #4	—	—	
NA	15	NA15 ⁽²⁾		#14 - #2	NA215		#14 - #2	NA3P15		#14 - 1/0
	20	NA20 ⁽²⁾			NA220			NA3P20		
	25	NA25			NA225			—	—	
	30	NA30			NA230			NA3P30		
	35	NA35			—	—		—	—	
	40	NA40			NA240			NA3P40		
	50	NA50		NA250		NA3P50				
	60	—	—	NA260		NA3P60				
	70	—	—	NA270		NA3P70				
	90	—	—	NA2P90		NA3P90				
	100	—	—	NA2P100		NA3P100				
	125	—	—	NA2P125		—	—			
	150	—	—	—	NA2P150 ¹		—	—		
							#4 - 2/0			

Notes:

1. NA2P150 rated 150A when used with copper conductor only
2. Switching duty approved breakers. Breakers are marked SWD
3. 2-pole and 3-pole breakers greater than 70A take 4 and 6 NA breaker positions respectively
4. Use solid conductor only when #14 wire is used
5. *

Stab-lok Main Circuit Breakers

Type	Amp Rating	2 Pole Cat No.	List Price	Lug Range	3 Pole Cat No.	List Price	Lug Range
NA	30-100	—	—	—	Use Breaker Table Above		
1C	30	1C30		#4-2/0	—	—	—
	40	1C40			—	—	—
	50	1C50			—	—	—
	60	1C60			—	—	—
	70	1C70			—	—	—
	90	1C90			—	—	—
	100	1C100			—	—	—
	125	1C125			—	—	—
2C	100	2C100		#4-250MCM	—	—	—
	125	2C125			—	—	—
	150	2C150			—	—	—
	175	2C175			—	—	—
	200	2C200			—	—	—



2C200

- * NC015/NC0215 Breaker Handle Colour - Blue
 NC020/NC0220 Breaker Handle Colour - Red
 NC030/NC0230 Breaker Handle Colour - Green
 NC040/NC0240 Breaker Handle Colour - Grey