



by Schneider Electric

Product availability: Stock - Normally stocked in distribution facility

Main

Commercial Status	Commercialised
Product or component type	Miniature circuit-breaker
Range of product	QO
Line Rated Current	20 A
Product certifications	CSA UL listed
System Voltage	240 V AC
Mounting mode	Plug-in
Poles description	3P
Short-circuit current	10 kA
Number of spaces required	3
Circuit breaker type	Standard
Circuit breaker application	HACR rated
Electrical connection	Pressure plate
AWG gauge	AWG 14...AWG 8 (copper or aluminium)
Accessory / separate part type	None

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with their own equipment. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information.

Ordering and shipping details

Category	00012 - QO 3 POLE CIRCUIT BREAKER
Discount Schedule	DE2A
GTIN	00785901400684
Nbr. of units in pkg.	3
Package weight(Lbs)	0.81
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Period	18 months
--------	-----------