

INF225

30:1 DUAL LASER
INFRARED THERMOMETER
W/ THERMOCOUPLE INPUT

NEW



Functions

- -76° to 1400°F Measurement range
- 30:1 Spot ratio
- Dual laser targeting
- Max / Min, differential, average
- Backlit display
- **3 Year limited warranty**

Includes

K-type thermocouple ATT29A
Batteries (2) AAA
Protective boot
Manual



INF165

INFRARED THERMOMETER



Functions

- -36.4 ~ 689°F (-38 ~ 365°C)
- 12:1 Distance to spot ratio
- Selectable emissivity (0.70, 0.95)
- Max value capture
- Auto off
- **3 Year limited warranty**

Includes

Batteries (2) AAA
Manual



INF195

INFRARED THERMOMETER
W/ THERMOCOUPLE INPUT



Functions

- -76° ~ 1022°F (-60° ~ 550°C)
- 12:1 Distance to spot ratio
- MIN / MAX, differential, average
- 3 emissivity levels: (0.30, 0.70, 0.95)
- Hi / low alarm (user adjustable)
- **3 Year limited warranty**

Includes

K-type thermocouple ATT29A
Batteries (2) AAA
Manual



PDT550

DIGITAL POCKET
THERMOMETER



Functions

- -58 ~ 572°F (-50 ~ 300°C)
- Built-in magnetic mount
- MIN / MAX record
- Dual purpose probe cover serves as thermometer extension
- Auto power off
- Quick and easy to read
- **3 Year limited warranty**

Includes

Batteries AB13

Sold in lots of five
Assorted color pack



PDT650

FOLDING POCKET
THERMOMETER



Functions

- -58 ~ 572°F (-50 ~ 300°C)
- Folding temperature probe
- Built-in magnetic mount
- MIN / MAX record
- Auto power off
- Large easy to read display
- **3 Year limited warranty**

Includes

Batteries AB13

Sold in lots of five



550B

DIGITAL POCKET
THERMOMETER



Functions

- -58° ~ 572°F
- Water resistant
- MIN / MAX
- Protective boot
- Magnetic mount
- Data hold
- Auto power off
- New ergonomic designed head
- Pen style sheath
- **3 Year limited warranty**

Includes

Batteries AB13

Sold in lots of five



DTK2
DIFFERENTIAL K-TYPE
THERMOCOUPLE
THERMOMETER

NEW



CE

- Functions**
- Dual input with differential (T1 - T2)
 - Min / Max capture (T1 & T2)
 - Auto power off with disable feature (15 minutes)
 - Large LCD screen
 - Complete with bead wire temperature probes and 9V battery
 - °C / °F select function
 - Magnetic mount
 - **3 Year limited warranty**

Includes

K-type bead probe (2)	ATT29A
Battery	9V
Pouch	
Manual	



DTK2KIT
DIFFERENTIAL
THERMOMETER KIT

NEW



CE

- Functions**
- Dual input with differential (T1 - T2)
 - Min / Max capture (T1 & T2)
 - Auto power off with disable feature (15 minutes)
 - Large LCD screen
 - Complete with bead wire temperature probes and 9V battery
 - °C / °F select function
 - Magnetic mount
 - **3 Year limited warranty**

Includes

K-type bead probe (2)	ATT29A
Soft carrying case	AC519
K-type pipe clamp adapter (2)	ATTPC2
Battery	9V
Manual	



DT15A
SINGLE INPUT THERMISTOR
DIGITAL THERMOMETER



- Functions**
- -58 ~ 571°F (-50 ~ 300°C)
 - MIN/MAX record
 - Backlit display
 - Data hold
 - Includes one replaceable, submersible metal probe
 - **3 Year limited warranty**

Includes

Thermistor probes	(2) ATT55A
Battery	(3) AAA
Manual	



DT20A
DUAL INPUT THERMISTOR
DIGITAL THERMOMETER



- Functions**
- -58 ~ 571°F (-50 to 300°C)
 - Dual probe inputs
 - Dual display lets you monitor any two of T1, T2 or differential (ΔT)
 - MIN/MAX record
 - Backlit display
 - Data hold
 - Includes two replaceable, submersible metal probes
 - **3 Year limited warranty**

Includes

Thermistor probes	(2) ATT55A
Battery	(3) AAA
Manual	



DTH10
DIGITAL THERMO-HYGROMETER



- Functions**
- Temperature in °F or °C
14 ~ 122°F (-10 ~ 50°C)
 - 5 ~ 95% Relative Humidity (RH)
 - Fast, accurate electronic sensor
 - Displays relative humidity and temperature at the same time
 - MIN/MAX record
 - Data hold
 - Auto power-off
 - **1 Year limited warranty**

Includes

Battery	(2) AAA
Manual	



DTH880
TEMPERATURE & HUMIDITY TESTER



- Functions**
- Temperature in °F or °C
32 ~ 122°F (0 ~ 50°C)
 - Relative humidity (RH) 25 ~ 95%
 - Comfort zone indicator
 - Displays relative humidity and temperature at the same time
 - MIN/MAX record
 - **1 Year limited warranty**

Includes

Battery	AAA
Manual	



ACCESSORIES

TEST LEADS

AAC	Push-on alligator clips with insulators for pointed test leads, 1 pair
AAC3	Screw-on alligator clips, 1 pair
ATL1	Standard Test Lead Tips
ATL2	Alligator Test Lead Tips
ATL3	Grabber Test Lead Tips
ATL4	Remote Alligator Test Lead Tips
ATL5	Back Probe Test Lead Tips
ATL6	Piercing Test Lead Tips
ATL55	UL listed insulated test leads for industry standard multimeters
ATL55A	UL CAT IV insulated test lead set, industry standard (G2 Phoenix)
ATL59	UL listed insulated test leads with alligator clips for Phoenix Clamp Meter Series™ (DL269 / DL279 / DL289)
ATL60	Test lead, microwave diode booster for all DMM (except DM5B)
ATL85	Vinyl insulated test leads for M1K, M20, M30
ATL135	Test leads for IRT3 & DMEG3
ATL190	Kelvin clip leads for CLM100 & CLM100B
ATL301KIT	ATLTX, ATL1, ATL2, ATL3, AC12
ATL501KIT	ATLTX, ATL1, ATL2, ATL3, ATL5, ATL6, AC12
ATLBPK	Back Probe Test Lead Kit (ATLTX, ATL5, AC12)
ATLFT	Fused Probe Test Leads Tips
ATLTX	Test Lead Kit Extension Wire



K-TYPE TEMPERATURE PROBES

Works with: DTK2, DT221, DT222, INF195, DL379, DL389, C125, C127, C155, C157, C091, DT301, DT302, DT304.

ATHA1	Gas valve K-Type thermocouple adapter
ATT29	4' Standard fiber glass coated (-40° to 950°F / -40° to 510°C)
ATT29A	4' Standard Fluoroplastic coated (-40° to 950°F / -40° to 510°C)
ATT29APACK	10 PACK 4' Standard Fluoroplastic coated
ATT36	8" Surface probe and handle (-40° to 950°F / -40° to 510°C)
ATT39	Storable Temperature probe for the DT301, DT302, DT304 (-40° to 950°F / -40° to 510°C)
ATT50	8" Liquid probe & handle (-40° to 1,550°F / -40° to 850°C)
ATT70	Temperature plug adapter for DMMs. DL259, DL289, DL279, DL269, DM397, DM393, UTL33T
ATT100	6" Liquid probe and handle (-40° to 950°F / -40° to 510°C)
ATTPC	Pipe clamp adapter for use with K-type inputs
ATTPC2	Clamp style adapter for use with K-type inputs
ATTEXT	10' Extension for K-type thermocouples

