

EXTREME™ SELF LIGHTING REPLACEMENT TIPS

Increase the range of your torch kit with additional self lighting tips. All TurboTorch® tips feature an orifice screw that can be easily removed for simple cleaning or replacement, extending the life of the tip.



PL-3A
(0386-0874)



PL-5A
(0386-0818)



PL-8A
(0386-0819)



PL-12A
(0386-0820)



3A-TE
(0386-1059)



5A-TE
(0386-1064)



8A-TE
(0386-1065)



12A-TE
(0386-1066)

AIR ACETYLENE

Tip No.	Tip Size		Gas Flow		Soft Solder		Silver Solder		Replacement Orifice		Replacement Tip	BTU
	IN.	MM	@14 PSI SCFH	(0.9 BAR) M3/HR	IN.	MM	IN.	MM				
PL-3A	3/16	5.0	3.6	0.31	1/4-1	10-25	1/8-1/2	3-12	OR-A3	0386-1001	3A-TE	1,280
PL-5A	1/4	6.4	5	0.42	3/4-1 1/2	20-40	1/4-3/4	10-20	OR-A8	0386-1003	5A-TE	2,080
PL-8A	5/16	7.9	7	0.59	1-2	25-50	1/2-1	15-30	-	0305-0511	8A-TE	2,520
PL-12A	3/8	9.5	9	0.76	2-4	50-90	1-2	25-50	OR-T-6	0386-1024	12A-TE	3,360

MAP-Pro™ & Propane

STANDARD

STANDARD PROPANE & MAP-PRO KITS:

Designed with the same Swirl Combustion Technology that is featured in the Proline Self Lighting Series, the manual series offers an economical alternative for use with Propane and MAP-Pro gases. A variety of tip sizes helps complete the job quickly and economically.



LP-1 KIT (0386-0247)

COMPONENTS

- R-LP Adjustable Regulator, CGA-510
- H-4 Handle
- H-12 Hose
- T-4 Tip
- T-6 Tip
- Soft solders to 6" (150 mm) with MAP-Pro
- Silver brazes to 4" (100 mm) with MAP-Pro
- Instruction Manual



Kit No.	Model	Regulator	Handle	Hose	Tip	
LP-1	0386-0247	RL-P (CGA-510)	H-4	H-12	T-4, T-6	Refer to tip chart below for soldering and brazing capacities
LP-2	0386-0007	RL-P (CGA-510)	H-4	H-12	T-3, T-5	
LP-3	0386-0006	RL-P (CGA-510)	H-4	H-12	T-4	



Tip No.	Tip Size		Air Propane	Air MAPP®	Copper Tubing Size Capacity Propane Gas				Copper Tubing Size Capacity MAPP® Gas				Replacement	
	IN.	MM	@24 PSI LBS/HR	@42 PSI LBS/HR	Soft Solder		Silver Solder		Soft Solder		Silver Solder		Orifice Model	
					IN	MM	IN	MM	IN	MM	IN	MM		
T-2	5/16	8.0	0.14	0.17	5/16-1/4	3-10	1/8-1/4	1-6	5/16-1/2	3-12	1/8-1/4	3-10	OR-A2	0386-1000
T-3	3/8	11.1	0.20	0.25	1/4-1	6-25	1/8-1/2	3-10	1/4-1 1/2	10-40	1/4-1/2	6-15	OR-T3	0386-1021
T-4	1/2	12.7	0.39	0.48	1/4-1 1/2	10-40	1/4-3/4	6-15	1/4-2 1/2	10-60	1/4-1 1/4	6-35	OR-A3	0386-1001
T-5	3/4	19.0	1.10	1.3	1 1/2-2 1/2	25-60	1/2-1 1/4	15-35	1-4	25-100	1/2-2	15-50	OR-A8	0386-1003
T-6	1	25.4	2.10	2.5	1 1/2-4	40-100	3/4-2	20-50	1 1/2-6	25-150	3/4-4	20-100	OR-T6	0386-1024

U.S. Customer Care: 800-238-0282 / FAX 800-535-0557