

PEX Press

For both residential and commercial applications, Viega PEX Press is the trusted way to join PEX tubing. As the world leader in press technology, Viega was the first to offer a press system to the PEX market. Combined with our revolutionary Viega ManaBloc water distribution system and the highest rated PEX tubing in the industry, Viega is a complete, premium plumbing solution.

FEATURES AND BENEFITS

- The original press fitting for PEX tubing
- Factory-assembled press fittings reduce installation errors on the job
- Available in sizes from 3/8" to 2"
- The only PEX fittings with the Viega Smart Connect feature
- Available in two materials, proprietary Zero Lead bronze and high-performance polymer
- Comprehensive 10-year transferable warranty

CODES AND STANDARDS

- ASTM E84: Specification for Surface Burning Characteristic
- ASTM F876: Standard Specification for PEX Tubing
- ASTM F877: Standard Specification for PEX Water Distribution System
- ASTM F1807/F2159: Standard Specification for PEX Insert Fittings
- ASTM F2023: Standard Test Method for Evaluating the Oxidative Resistance of Cross-linked Polyethylene PEX Tubing and Systems to Hot Chlorinated Water
- AWWA C904: Cross-linked Polyethylene (PEX) Pressure Pipe for water service
- CAN/ULC S101: Standard Method of Test for Surface Burning Characteristics
- CAN/ULC S102.2: Standard Method of Test for Surface Burning Characteristics
- CSA International: Canadian Standard Association
- CSA B137.5: Standard Specification for PEX tubing systems in pressure applications
- IAPMO: Uniform Plumbing Code
- ICC: International Plumbing Code
- NSF/ANSI 61: Drinking Water System Components – Health Effects
- NSF/ANSI 61G: Lead Content Evaluation Procedure to meet < 0.25% average lead content
- NSF/ANSI 14: Plastics Piping System Components and Related Materials
- NSPC: National Standard Plumbing Code
- UL 1821: Thermoplastic Sprinkler Pipe and Fittings for Fire Protection Service

ZERO LEAD

References to Zero Lead throughout this publication mean product meeting the requirements of NSF 61-G through testing under NSF/ANSI Standard 372 (0.25% or less percent maximum weighted average lead content).

NOTE

A Green Dot on a Viega PEX Press fitting indicates the Smart Connect feature.

Tubing



ViegaPEX Ultra tubing

- PEX
- Coil
- Technical Data
- PEX designation code 5306
- UV resistance 6 months
- ASTM F876, ASTM F877
- Model V5001**

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	100	red	5.000	1	32101 ¹	1
3/8	500	red	21.000	1	32105 ¹	1
3/8	1000	red	42.000	1	32100	1
1/2	100	red	5.800	1	32121 ¹	1
1/2	300	red	17.100	1	32123 ¹	1
1/2	500	red	28.000	1	32125 ¹	1
1/2	1000	red	58.000	1	32120	1
3/4	100	red	11.000	1	32141 ¹	1
3/4	300	red	32.100	1	32143 ¹	1
3/4	500	red	53.000	1	32145 ¹	1
1	100	red	16.900	1	33323 ¹	1
1	300	red	50.700	1	32163	1
1	500	red	88.000	1	32165	1

¹⁾ center pull coil



ViegaPEX Ultra tubing

- PEX
- Straight length
- Technical Data
- PEX designation code 5306
- UV resistance 6 months
- ASTM F876, ASTM F877
- Model V5001.5**

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	red	0.540	50	33272	1
1/2	20	red	1.060	50	33120	1
3/4	10	red	1.020	25	33275	1
3/4	20	red	2.040	25	33145	1
1	20	red	3.420	5	33270	1



ViegaPEX Ultra tubing

- PEX
- Coil
- Technical Data
- PEX designation code 5306
- UV resistance 6 months
- ASTM F876, ASTM F877
- Model V5002**

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	100	blue	5.000	1	32201 ¹	1
3/8	500	blue	21.000	1	32205 ¹	1
3/8	1000	blue	42.000	1	32200	1
1/2	100	blue	5.300	1	32221 ¹	1
1/2	300	blue	17.100	1	32223 ¹	1
1/2	500	blue	26.500	1	32225 ¹	1
1/2	1000	blue	55.000	1	32220	1
3/4	100	blue	11.000	1	32241 ¹	1
3/4	300	blue	32.100	1	32243 ¹	1
3/4	500	blue	53.000	1	32245 ¹	1
1	100	blue	17.000	1	32266	1
1	300	blue	50.700	1	32263	1
1	500	blue	88.000	1	32265	1

¹⁾ center pull coil



ViegaPEX Ultra tubing

- PEX
- Straight length
- Technical Data
- PEX designation code 5306
- UV resistance 6 months
- ASTM F876, ASTM F877
- Model V5002.5**

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	blue	0.540	50	33274	1
1/2	20	blue	1.060	50	33240	1
3/4	10	blue	1.020	25	33277	1
3/4	20	blue	2.040	25	33265	1
1	20	blue	3.420	5	33271	1



ViegaPEX Ultra tubing

- For installation between studs
- PEX
- ManaPac
- components
- Recycled plastic reels
- Technical Data
- PEX designation code 5306
- UV resistance 6 months
- ASTM F876, ASTM F877
- Model V5004**

d	L [ft]	Reel(s)	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	2	red/blue	58.000	1	32300 ¹	1
3/8	500	1	blue	28.000	1	32905	1
3/8	500	1	red	28.000	1	32805	1
1/2	300	2	red/blue	48.000	1	32326 ¹	1
1/2	300	1	blue	23.100	1	32923	1
1/2	300	1	red	23.100	1	32823	1

¹⁾ Available while supplies last

PEX Crimp

Offering the reliability and quality needed for potable water systems, Viega PEX Crimp fittings are part of our complete plumbing solution. Matched with our revolutionary Viega ManaBloc water distribution system and the highest rated PEX tubing in the industry, Viega PEX Crimp fittings are a time-tested method of joining PEX.

FEATURES AND BENEFITS

- EcoBrass® fittings provide better corrosion resistance than other brass fittings
- High-performance PolyAlloy fittings are made in the USA
- Peace of mind from durable materials and quality manufacturing
- In sizes 3/8" to 1"
- Comprehensive 10-year transferable warranty

CODES AND STANDARDS

- ASTM E84: Specification for Surface Burning Characteristics
- ASTM F876: Standard Specification for PEX Tubing
- ASTM F877: Standard Specification for PEX Water Distribution System
- ASTM F1807/F2159: Standard Specification for PEX Insert Fittings
- ASTM F2023: Standard Test Method for Evaluating the Oxidative Resistance of Cross-linked Polyethylene PEX Tubing and Systems to Hot Chlorinated Water
- AWWA C904: Cross-linked Polyethylene (PEX) Pressure Pipe for water service
- CAN/ULC S101: Standard Method of Test for Surface Burning Characteristics
- CAN/ULC S102.2: Standard Method of Test for Surface Burning Characteristics
- CSA International: Canadian Standard Association
- CSA B137.5: Standard Specification for PEX tubing systems in pressure applications
- ICC: International Plumbing Code
- IAPMO: Uniform Plumbing Code
- NSF/ANSI 61: Drinking Water System Components - Health Effects
- NSF/ANSI 61G: Lead Content Evaluation Procedure to meet < 0.25% average lead content
- NSF/ANSI 14: Plastics Piping System Components and Related Materials
- NSPC: National Standard Plumbing Code
- UL 1821: Thermoplastic Sprinkler Pipe and Fittings for Fire Protection Service

ZERO LEAD

References to Zero Lead throughout this publication mean product meeting the requirements of NSF 61-G through testing under NSF/ANSI Standard 372 (0.25% or less percent maximum weighted average lead content).

Tubing



ViegaPEX Ultra tubing

- PEX
- Coil
- Technical Data
- PEX designation code 5306
- UV resistance 6 months
- ASTM F876, ASTM F877
- Model V5001**

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	100	red	5.000	1	32101 ¹	1
3/8	500	red	21.000	1	32105 ¹	1
3/8	1000	red	42.000	1	32100	1
1/2	100	red	5.800	1	32121 ¹	1
1/2	300	red	17.100	1	32123 ¹	1
1/2	500	red	28.000	1	32125 ¹	1
1/2	1000	red	58.000	1	32120	1
3/4	100	red	11.000	1	32141 ¹	1
3/4	300	red	32.100	1	32143 ¹	1
3/4	500	red	53.000	1	32145 ¹	1
1	100	red	16.900	1	33323 ¹	1
1	300	red	50.700	1	32163	1
1	500	red	88.000	1	32165	1

¹⁾ center pull coil



ViegaPEX Ultra tubing

- PEX
- Straight length
- Technical Data
- PEX designation code 5306
- UV resistance 6 months
- ASTM F876, ASTM F877
- Model V5001.5**

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	red	0.540	50	33272	1
1/2	20	red	1.060	50	33120	1
3/4	10	red	1.020	25	33275	1
3/4	20	red	2.040	25	33145	1
1	20	red	3.420	5	33270	1



ViegaPEX Ultra tubing

- PEX
- Coil
- Technical Data
- PEX designation code 5306
- UV resistance 6 months
- ASTM F876, ASTM F877
- Model V5002**

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	100	blue	5.000	1	32201 ¹	1
3/8	500	blue	21.000	1	32205 ¹	1
3/8	1000	blue	42.000	1	32200	1
1/2	100	blue	5.300	1	32221 ¹	1
1/2	300	blue	17.100	1	32223 ¹	1
1/2	500	blue	26.500	1	32225 ¹	1
1/2	1000	blue	55.000	1	32220	1
3/4	100	blue	11.000	1	32241 ¹	1
3/4	300	blue	32.100	1	32243 ¹	1
3/4	500	blue	53.000	1	32245 ¹	1
1	100	blue	17.000	1	32266	1
1	300	blue	50.700	1	32263	1
1	500	blue	88.000	1	32265	1

¹⁾ center pull coil



ViegaPEX Ultra tubing

- PEX
- Straight length
- Technical Data
- PEX designation code 5306
- UV resistance 6 months
- ASTM F876, ASTM F877
- Model V5002.5**

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	blue	0.540	50	33274	1
1/2	20	blue	1.060	50	33240	1
3/4	10	blue	1.020	25	33277	1
3/4	20	blue	2.040	25	33265	1
1	20	blue	3.420	5	33271	1



ViegaPEX Ultra tubing

- For installation between studs
- PEX
- ManaPac
- components
- Recycled plastic reels
- Technical Data
- PEX designation code 5306
- UV resistance 6 months
- ASTM F876, ASTM F877
- Model V5004**

d	L [ft]	Reel(s)	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	2	red/blue	58.000	1	32300 ¹	1
3/8	500	1	blue	28.000	1	32905	1
3/8	500	1	red	28.000	1	32805	1
1/2	300	2	red/blue	48.000	1	32326 ¹	1
1/2	300	1	blue	23.100	1	32923	1
1/2	300	1	red	23.100	1	32823	1

¹⁾ Available while supplies last