
# **Thermostat Wire**

## 20/2 Solid Riser Rated Thermostat Wire



#### **Compliance & Certifications**

COMPLIANCE					
RoHS	UL listed	NEC			
CERTIFICATIONS					
UL Standard 13		UL 1685 Vertical Tray			
UL Listed Type CL2R		NEC Article 725			

PHYSICAL SPECIFICATIONS	
CONDUCTOR MATERIAL	Solid Bare Copper
CONDUCTOR SIZE	20 AWG
# OF CONDUCTORS	2
CONDUCTOR DIAMETER	0.031 in.
INSULATING MATERIAL	Polypropylene
INSULATION DIAMETER	0.049 in.
INSULATION NOMINAL THICKNESS	0.008 in.
NUMBER OF INSULATIONS	2
INSULATION COLORS	Red, White
JACKET MATERIAL	PVC
JACKET COLOR	Brown
JACKET DIAMETER	0.136 in.
JACKET NOMINAL THICKNESS	0.016 in.
JACKET FLAME RATE	CL2R
RIPCORD	Nylon



#### Features & Benefits

- $\cdot$  Temperature rating from -20 to 60° C
- · Operating voltage up to 300 Volts maximum
- · Nominal capacitance of 22 pf/ft
- · Characteristic impedance of 100 Ohms nom.
- · DC resistance of 10.3 Ohms/M' at 20° C
- Suitable for any type of installation requiring a 20 gauge 2 conductor thermostat wire

## **Ordering Information**

PART NUMBER	CONDUCTORS	AWG	# CONDUCTORS	RATING	COLOR	PACKING
HT202-02556	Solid Bare Copper	20	2	CL2R	Brown	Spool

## 20/4 Solid Riser Rated Thermostat Wire



### **Compliance & Certifications**

COMPLIANCE					
RoHS	UL listed		NEC		
CERTIFICATIONS					
UL Standard 13		UL 1685 Vertical Tray			
UL Listed Type CL2R		NEC Article 725			

PHYSICAL SPECIFICATIONS				
CONDUCTOR MATERIAL	Solid Bare Copper			
CONDUCTOR SIZE	20 AWG			
# OF CONDUCTORS	4			
CONDUCTOR DIAMETER	0.031 in.			
INSULATING MATERIAL	Polypropylene			
INSULATION DIAMETER	0.057 in.			
INSULATION NOMINAL THICKNESS	0.008 in.			
NUMBER OF INSULATIONS	4			
INSULATION COLORS	Red, White, Green, Blue			
JACKET MATERIAL	PVC			
JACKET COLOR	Brown			
JACKET DIAMETER	0.124 in.			
JACKET NOMINAL THICKNESS	0.016 in.			
JACKET FLAME RATE	CL2R			
RIPCORD	Nylon			



#### Features & Benefits

- · Temperature rating from -20 to 60° C
- · Operating voltage up to 300 Volts maximum
- · Nominal capacitance of 22 pf/ft
- · Characteristic impedance of 100 Ohms nom.
- · DC resistance of 10.3 Ohms/M' at 20° C
- Suitable for any type of installation requiring a 20 gauge 4 conductor thermostat wire

## **Ordering Information**

PART NUMBER	CONDUCTORS	AWG	# CONDUCTORS	RATING	COLOR	PACKING
HT204-02558	Solid Bare Copper	20	4	CL2R	Brown	Spool

