For Residential and Commercial Applications

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

Series 26A, 263A Small Pressure Regulators

Sizes: 26A: ¹/₈" – ¹/₂" (3 – 15mm) 263A: ¹/₄" – ¹/₂" (8 – 15mm)

Series 26A, 263A Small Pressure Regulators are general purpose pressure regulators for water and no. 2 fuel oil. These regulators are ideal for use in beverage dispensers, ice cube machines, paint sprayers, humidifiers and other similar applications.

Features

- Rugged forged brass body
- Tee handle adjustment
- Oversized orifice

Models

26A 2-way regulator **263A** 3-way regulator

Materials

Body:	Brass
Spring Cage:	Aluminum
Disc:	Buna-N stainless steel
Diaphragm:	Reinforced Buna-N


Pressure – Temperature

Maximum Temperature: 140°F (60°C) Maximum Working Pressure: 300psi (21 bars) Reduced Pressure Range:


Range		Std. Set at		
psi	bars	psi	bars	
1 – 25	0.1 – 1.7	10	0.7	
3 – 50	0.2 - 3.4	15	1.0	
10 – 125	0.7 - 8.6	25	1.7	
50 – 175	3.4 – 12.1	50	3.4	


Options

- G Pressure gauge
- SS All stainless steel construction, (see literature ES-SS-263AP)
- X Slotted adjusting screw



Capacity





263A

3-Way

Dimensions – Weights

Model	Size	(DN)	N) A		С		Weight	
	in	mm	in	mm	in	mm	lbs	kgs
26A	1⁄8	3	21/8	54	43⁄8	111	1	.45
26A/263A	1⁄4	8	21/8	54	43⁄8	111	1	.45
26A/263A	3⁄8	10	21/8	54	43/8	111	1	.45
26A/263A	1/2	15	21/8	54	43⁄8	111	1	.45

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: 815 Chestnut St., No. Andover, MA 01845-6098;www.wattsreg.com Canada: 5435 North Service Rd., Burlington, ONT. L7L 5H7;www.wattscanada.ca <u>SO</u>9001

CERTIFIED