

LEADED SOLDER

FOR USE ONLY IN NON-POTABLE WATER APPLICATIONS

50/50 LEADED

50% Tin, 50% Lead Solder

WOR PROD NO	LENOX PROD NO	DESCRIPTION	WEIGHT		DIAMETER		CARTON QTY
			LB	G	IN	MM	
331753	WS10098	50/50 Wire Spool	1	454	.125	3.2	50
331887	WS10305	50/50 Wire Spool	1/4	113	.125	3.2	50
331886	WS10306	50/50 Wire Spool	1/2	227	.125	3.2	50
331888	WS10100	50/50 Wire Spool	5	2270	.125	3.2	10

40/60 LEADED

40% Tin, 60% Lead Solder

WOR PROD NO	LENOX PROD NO	DESCRIPTION	WEIGHT		DIAMETER		CARTON QTY
			LB	G	IN	MM	
331881	WS10307	40/60 Wire Spool	1/2	227	.125	3.2	50
331850	WS10088	40/60 Wire Spool	1	454	.125	3.2	50

60/40 LEADED

60% Tin, 40% Lead Solder

WOR PROD NO	LENOX PROD NO	DESCRIPTION	WEIGHT		DIAMETER		CARTON QTY
			LB	G	IN	MM	
331858	WS10261	60/40 Wire Spool	1	454	.125	3.2	50



EXTRUDED LEADED BARS

Various Ratios

WOR PROD NO	LENOX PROD NO	DESCRIPTION	WEIGHT		DIAMETER		CARTON QTY
			LB	G	IN	MM	
331851	WS10257	50/50 Extruded Bar	1	454	—	—	50
331885	WS10161	50/50 Extruded Meter Bar	1/2	227	—	—	50
331882	WS10297	50/50 Extruded Tri Bar	1/4	113	1/4	6.4	50
331883	WS10298	50/50 Extruded Tri Bar	13/32	184	5/16	7.9	50
331884	WS10299	50/50 Extruded Tri Bar	1/2	227	7/16	11.1	50
331853	WS10069	60/40 Extruded Bar	1	454	—	—	20
331848	WS10300	40/60 Extruded Bar	1	454	—	—	50
331845	WS10316	30/70 Extruded Bar	1	454	—	—	50

SPECIALTY LEADED SOLDER

FOR USE ONLY IN NON-POTABLE WATER APPLICATIONS

ACID CORE LEADED

Use for tin repairs, sheet metal, auto radiators, metal gutters, and non-electrical and non-plumbing applications

Tin-Lead Acid Core Solder

WOR PROD NO	LENOX PROD NO	DESCRIPTION	WEIGHT		DIAMETER		CARTON QTY
			LB	G	IN	MM	
331846	WS10317	30/70 Acid Core Wire Spool	1	454	.125	3.2	50
331852	WS10314	60/40 Acid Core Wire Spool	1	454	.062	1.6	50
331847	WS10315	40/60 Acid Core Wire Spool	1	454	.062	1.6	50
331880	WS10196	3/2/95 Acid Core Wire Spool	1/2	227	.125	3.2	50

ROSIN CORE LEADED

Use for speaker wire, motors, appliances and general electronic repairs Tin-Lead Rosin Core Solder

WOR PROD NO	LENOX PROD NO	DESCRIPTION	WEIGHT		DIAMETER		CARTON QTY
			LB	G	IN	MM	
331855	WS10312	60/40 Rosin Core Wire Spool	1	454	.062	1.6	50
331856	WS10318	60/40 Rosin Core Wire Spool	1	454	.031	.8	50
331854	WS10321	60/40 Rosin Core Wire Spool	1	454	.100	2.5	50
331857	WS10322	60/40 Rosin Core Wire Spool	1	454	.125	3.2	50
331849	WS10313	40/60 Rosin Core Wire Spool	1	454	.062	1.6	50

