



## WARDFLEX® Stripwound Conduit

Ward Manufacturing, LLC.

117 Gulick Street  
 Blossburg, PA 16912  
 Tel. (800)248-1027  
 www.wardmfg.com

### Description:

Stripwound metal conduit can be used to protect WARDFLEX®/WARDFLEX® MAX CSST when the tubing is in a concealed location and cannot be displaced a minimum of 3" from a puncture threat or the distance between supports is less than 24 inches. Stripwound conduit cannot be used as a substitute for striker plates where tubing passes through structural members.

### Features:

- Easy Installation
- Available for tubing sizes 3/8" through 1-1/4"
- Available in 1 ft lengths or 50 ft coils

### Listings:

- CSA: File# 112940\_0\_000



### Technical Data:

#### Material

Conduit	Galvanized Steel
---------	------------------

#### Dimensions

Price Sheet Item #	For CSST Size	Nominal Size	Strip Thickness	Length	Approximate Weight (lbs)
620	3/8"	3/4"	0.01"	50'	9.00
621	3/8"	3/4"	0.01"	1'	0.29
622	1/2"	1"	0.01"	50'	20.00
623	1/2"	1"	0.01"	1'	0.40
624	3/4"	1-1/4"	0.01"	50'	24.00
625	3/4"	1-1/4"	0.01"	1'	0.49
626	1"	1-1/2"	0.01"	50'	28.00
627	1"	1-1/2"	0.01"	1'	0.64
628	1-1/4"	2"	0.01"	50'	35.00
629	1-1/4"	2"	0.01"	1'	0.68